

PRODUCT INFORMATION

METALLOTION PROTEC CE15L SPRAY

ANTI-SPATTER SPRAY, NON-FLAMMABLE

PROPERTIES

- Metallotion PROTEC CE15L reliably **protects from welding spatter**, for application to workpieces, equipment and tools (welding guns)
- Optimum component protection for **steel and stainless steel**
- Features an **integrated cleaning function** (degreasing)
- **No silicone, non-flammable and biodegradable**

ADVANTAGES

- **Suitable for all conventional coating methods** (e.g. galvanising, powder coating, electroplating, painting, etc.)
- Ensures a **SAFE** workplace, for instance compared with flammable sprays
- **Perfectly suitable to be welded over**
- **Effective when wet or dry** (long-term protection)

CUSTOMER BENEFITS

- **Increased productivity** — no need for reworking
- **Increased quality** with spatter-free metal surfaces
- **2-3 times the range per can** with dual chamber spray system (bag-in-can technology)
- Maximum **process safety + safe for users and the environment**

APPLICATION

Apply to parts and equipment **from a distance of approximately 20cm** before welding or cutting.

Spray burners and gas nozzles from a short distance, apply when the nozzle is still hot to obtain ideal results.

Shake before use.

Protect from frost.

KEY DATA

Effective ingredient type:	Herbal fatty acid products with fatty alcohol ethoxylates in emulsion on water basis	Flash point:	n. a.
Density (20°C):	0,98 g/ml	PH value	7,2
Viskosität (20°C)	9,5 sec DIN 53211/4	Shelf life	Min. 12 months
Trading Unit	Bag in Can Aerosol, ID-No. A003.004	Safety datasheet	No. 01Ds5 (www.protec-austria.com)